



ProMix™ 3KS

Three-Component Electronic Proportioning System



Upgrade your system today with the ProMix™ 3KS

- Precision mixing of three component materials
- Manual or automatic operation
- Up to 25 colours, 4 catalysts, and 4 reducers in modular colour change system
- Intrinsically safe fluid panel for operation in hazardous areas
- Optimized flushing sequences including third flush option
- Purchase with a 2KS system or upgrade an existing 2KS system

For more information, visit our website at www.graco.com

PROVEN QUALITY. LEADING TECHNOLOGY.



ProMix™ 3KS

ProMix™ 3KS Example System

Ordering Information Accessories

Cables

123277.....	1,82 M (6 ft) Yellow Colour Change/Booth Control
123280.....	15 M (50 ft) Yellow Colour Change/Booth Control
123273.....	3 M (10 ft) Green CAN Cable
123274.....	7,5 M (25 ft) Green CAN Cable
123271.....	15 M (50 ft) Red Power Cable
123272.....	30 M (100 ft) Red Power Cable

Miscellaneous Kits

16A732	3K Floor Stand Extension Extends 15V950 2KS floor stand for 3KS use
--------------	--



Step 1: Identify

Specify your base system.

Refer to ProMix 2KS brochure (339996) for more information

Step 2: Upgrade!

Choose the ProMix 3KS Module to fit your system.

T	K	X	X	0	0
↑	↑	↑	↑	↑	↑
Three	Component	Meter	Colour Valves	0	0

T	K	Meter	Colour Valves	0	0
T	K	0 = No Meter	0 = No Valves (single colour)	0	0
		1 = G3000	1 = 2 Colour LP		
		2 = G3000 HR	2 = 4 Colour LP		
		3 = 1/8" Coriolis	3 = 2 Colour HP		
		4 = S3000	4 = 4 Colour HP		

Technical Data

Mix ratio range*

Sequential dosing	1st stage: 0.1:1 To 50:1
	2nd stage: 0.1:1 To 50:1
Dynamic dosing	1st stage: 0.1:1 To 30:1
	2nd stage: 0.1:1 To 30:1

Ratio accuracy..... up to + 1% minimum (user selectable)

External power supply requirements.....85-250 Vac, 50/60 Hz. 2 Amps max draw,
15 amp circuitbreaker required,
2,5 mm² (8 to 14 AWG) power supply wire gauge

Operating temperature range.....5 to 50°C (41 to 122°F)

Noise level

Sound pressure levelbelow 70 dB(A)

Sound power levelbelow 85 dB(A)

Wetted parts..... 303 SST, 17-4 SST, PTFE, Perfluoroelastomer,
tungsten carbide with nickel binder

Weight

3ks wall fluid panel..... 14.8 Kg (32.6 Lb)

Power/barrier assy..... 6.9 Kg (15.2 Lb)

*Ratio ranges are dependent on flow rate, dose size and meter resolution

GRACO N.V. Industrieterrein Oude Bunders
Slakweidestraat 31 • B-3630 Maasmechelen
Tel: +32 (89) 770 700 • Fax: +32 (89) 770 777
E-mail: info@graco.be • http://www.graco.com

©2010 Graco Inc. Form No. 344807E Rev. A 03/10 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.